

Attestation of Conformity

No. N8A 128543 0002 Rev. 00

Holder of Attestation: Swiss Luxra Holding AG

Riedstrasse 7 6330 Cham SWITZERLAND

Product: Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062492801-00

Date, 2024-10-10

(Zhulin Zhang)

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Attestation of Conformity

No. N8A 128543 0002 Rev. 00

Model(s):

Luxra Pure LX-xxxN-50HC-BFGG (xxx=480-510 in step of 5W) Luxra Pure LX-xxxN-45HC-BFGG (xxx=430-460 in step of 5W) Luxra Pure LX-xxxN-40HC-BFGG (xxx=385-400 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG (xxx=635-675 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG (xxx=580-615 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG (xxx=520-550 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG (xxx=465-480 in step of 5W) Luxra Pure LX-xxxN-44HC-BFGG (xxx=425-440 in step of 5W) Luxra Pure LX-xxxN-72HC-BFGG (xxx=530-550 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG (xxx=485-500 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG (xxx=445-455 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG (xxx=400-410 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG (xxx=355-365 in step of 5W) Luxra Pure LX-xxxN-72HC-BFGG (xxx=430-455 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG (xxx=395-415 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG (xxx=360-380 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(TOPCON) (xxx=675-700 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(TOPCON) (xxx=615-635 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(TOPCON) (xxx=555-570 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG(TOPCON) (xxx=490-505 in step of 5W) Luxra Pure LX-xxxN-78HC-BFGG(TOPCON) (xxx=595-625 in step of 5W) Luxra Pure LX-xxxN-72HC-BFGG(TOPCON) (xxx=550-620 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(TOPCON) (xxx=505-570 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(TOPCON) (xxx=460-520 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(TOPCON) (xxx=415-465 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(HJT) (xxx=675-715 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(HJT) (xxx=615-650 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(HJT) (xxx=555-585 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG(HJT) (xxx=490-520 in step of 5W) Luxra Pure LX-xxxN-72HC-BFGG(HJT) (xxx=550-580 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(HJT) (xxx=505-530 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(HJT) (xxx=460-480 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(HJT) (xxx=415-435 in step of 5W)

Luxra Pure LX-xxxN-55HC-BFGG (xxx=525-560 in step of 5W)

Black series

Luxra Pure LX-xxxN-55HC-BFGG(black) (xxx=525-560 in step of 5W) Luxra Pure LX-xxxN-50HC-BFGG(black) (xxx=480-510 in step of 5W) Luxra Pure LX-xxxN-45HC-BFGG(black) (xxx=430-460 in step of 5W) Luxra Pure LX-xxxN-40HC-BFGG(black) (xxx=385-400 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(black) (xxx=635-675 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(black) (xxx=580-615 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(black) (xxx=520-550 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG(black) (xxx=465-480 in step of 5W) Luxra Pure LX-xxxN-44HC-BFGG(black) (xxx=425-440 in step of 5W) Luxra Pure LX-xxxN-72HC-BFGG(black) (xxx=530-550 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(black) (xxx=485-500 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(black) (xxx=445-455 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(black) (xxx=400-410 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG(black) (xxx=355-365 in step of 5W) Luxra Pure LX-xxxN-72HC-BFGG(black) (xxx=430-455 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(black) (xxx=395-415 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(black) (xxx=360-380 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(TOPCON)(black) (xxx=675-700 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(TOPCON)(black) (xxx=615-635 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(TOPCON)(black) (xxx=555-570 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG(TOPCON)(black) (xxx=490-505 in step of 5W) Luxra Pure LX-xxxN-78HC-BFGG(TOPCON)(black)

Page 2 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Attestation of Conformity

No. N8A 128543 0002 Rev. 00

(xxx=595-625 in step of 5W)

Luxra Pure LX-xxxN-72HC-BFGG(TOPCON)(black)

(xxx=550-620 in step of 5W)

Luxra Pure LX-xxxN-66HC-BFGG(TOPCON)(black)

(xxx=505-570 in step of 5W)

Luxra Pure LX-xxxN-60HC-BFGG(TOPCON)(black)

(xxx=460-520 in step of 5W)

Luxra Pure LX-xxxN-54HC-BFGG(TOPCON)(black)

(xxx=415-465 in step of 5W)

Luxra Pure LX-xxxN-66HC-BFGG(HJT)(black) (xxx=675-715 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(HJT)(black) (xxx=615-650 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(HJT)(black) (xxx=555-585 in step of 5W) Luxra Pure LX-xxxN-48HC-BFGG(HJT)(black) (xxx=490-520 in step of 5W) Luxra Pure LX-xxxN-72HC-BFGG(HJT)(black) (xxx=550-580 in step of 5W) Luxra Pure LX-xxxN-66HC-BFGG(HJT)(black) (xxx=505-530 in step of 5W) Luxra Pure LX-xxxN-60HC-BFGG(HJT)(black) (xxx=460-480 in step of 5W) Luxra Pure LX-xxxN-54HC-BFGG(HJT)(black) (xxx=415-435 in step of 5W)

xxx is standing for rated output power at STC

Parameters:

Safety Class: Class II

Max. System Voltage: 1500V DC

Test Laboratory: Changzhou HuaYang Inspection and Testing Technology Co., Ltd.

No.8 Lanxiang Road

Wujin Economic Development Zone

Changzhou, Jiangsu, China

Framed, double glass Construction:

with Junction box, cable and connector.

Fire Safety Class: Class C according to UL790

EN IEC 61730-1:2018 **Tested**

EN IEC 61730-1:2018/AC:2018-06 according to:

EN IEC 61730-2:2018

EN IEC 61730-2:2018/AC:2018-06

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

